

ROCKBOND SCP LTD

FORMULATORS, MANUFACTURERS AND CONSULTANTS OF SPECIAL CONCRETE PRODUCTS

Newton's Farm Estate, Wissington, Nayland, Suffolk.CO6 4LX, England

Telephone: 01206 265116 Email: info@rockbond.co.uk

Website: www.rockbond.co.uk

MATERIAL SAFETY DATA SHEET

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION/COMPANY:

PRODUCT: ROCKBOND POLYMER LATICES AND COATINGS

COMPANY: Rockbond SCP Ltd.,
Newton's Farm Estate,
Wissington, Nayland,
CO6 4LX,
Suffolk,
England

Telephone: 01206 265116,
Facsimile: 01206 265117,

[Email: info@rockbond.co.uk](mailto:info@rockbond.co.uk)
[Website: www.rockbond.co.uk](http://www.rockbond.co.uk)

2. COMPOSITION/INFORMATION ON INGREDIENTS:

Rockbond Polymer Latices and Coatings are blends of polymer and co-polymer solid particles dispersed in water. The polymers are based on pure acrylic and acrylic esters, styrene, butadiene, natural rubber and bitumen.

3. HAZARDS IDENTIFICATION:

Non hazardous. Water based. Can be slightly irritating to the skin and eyes.
Dispersions do not present any particular fire hazard.

4. FIRST AID MEASURES:

Inhalation: Should the odour, or vapours, in the latex cause discomfort, which is unlikely, move the patient to a source of fresh air.

Skin: If skin contact occurs, thoroughly wash the affected area with running water. Remove contaminated clothing immediately.

Eyes: Eyes that have become affected with latex must be immediately and thoroughly rinsed with running water for several minutes with the eyelids fully open. In severe cases, seek medical advice without delay.

Ingestion: If a small amount is swallowed, give the person a glass of water to drink. If a large amount is taken, seek immediate medical attention. Do not induce vomiting. Reassure the individual that there is no serious poisoning hazard, and keep him quiet and calm.

5. FIRE FIGHTING MEASURES:

Suitable extinguishing media: Dry powder, foam, carbon dioxide or water spray
Special exposure hazards: Can give off dense black smoke and hazardous combustion products.

SAFETY DATA SHEET, ROCKBOND POLYMER LATICES AND COATINGS CONTINUED...

6. ACCIDENTAL RELEASE MEASURES:

Personal precautions: Wear protective clothing.
Environmental precautions: Do not allow spillages to enter watercourses or streams.
Methods for cleaning up: Soak up spillages on an absorbent material and place in a suitable container for disposal.

7. HANDLING AND STORAGE:

Handling: Wear protective clothing and eye protection when handling dispersions.
Storage: Store in a cool, dry, dark place.
Protect from frost.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION:

Engineering measures: No special measures required
Recommended personal protection: Wear suitable waterproof clothing, PVC gloves and side protected goggles.

9. PHYSICAL AND CHEMICAL PROPERTIES:

Appearance:	Liquid or thixotropic gels	Flash point:	Not applicable
Colour:	White or pigmented	Flammability:	Not applicable
	The bituminous latex is black	Explosive properties:	Not applicable
Odour:	Slight	Oxidising properties:	None
pH:	6.5 to 9.0	Vapour pressure:	As water
Boiling point:	100°C approx	Relative density:	0.98 to 1.20
Melting point:	0°C approx	Solubility in water:	Miscible

10. STABILITY AND REACTIVITY:

Stability: Stable under normal conditions of use. Protect from frost.
Materials to avoid: Strong oxidising agents and acids
Hazardous decomposition products: None. Combustion can produce carbon monoxide and carbon dioxide

11. TOXICOLOGICAL INFORMATION:

Acute toxicity: LD50 Oral rat: >2000mg/kg
Effects of exposure and symptoms: May cause irritation to eyes and skin.
May cause irritation to the digestive system.

12. ECOLOGICAL INFORMATION:

Aquatic toxicity: Under normal conditions, there is no indication that the liquid can be considered as a health risk. Once dry, the hardened polymer film will not re-emulsify.
Environmental effects: Water for sewerage treatment that has been contaminated with small quantities of the product will not effect the biomass. The polymer will be largely absorbed on the sludge and removed from the waste water.

SAFETY DATA SHEET, ROCKBOND POLYMER LATICES AND COATINGS CONTINUED...

13. DISPOSAL CONSIDERATIONS:

Disposal of materials:	In accordance with local authority regulations
Disposal of packaging:	In accordance with local authority regulations

14. TRANSPORT INFORMATION:

Not classified as a hazardous material for transportation.

15. REGULATORY INFORMATION:

Labelling:	Not applicable
Safety phases:	No safety phases
Risk phases:	No risk phases

16. OTHER INFORMATION:

The safety data sheet applies to the following ROCKBOND SPECIAL CONCRETE PRODUCTS:

ROCKBOND PRIMER LATEX CONCENTRATE (RB PLC)
ROCKBOND PRIMER LATEX (RB PL)
ROCKBOND FLEXIBLE LATEX (RB FL)
ROCKBOND PURE ACRYLIC LATEX (RB PAL)
ROCKBOND ACRYLIC LATEX (RB AL)
ROCKBOND SBR LATEX (RB SBRL)
ROCKBOND BITUMINOUS LATEX (RB BL)
ROCKBOND RUBBER LATEX (RB RL)
ROCKBOND CURE CONCENTRATE (RB CC)
ROCKBOND CURE (RB C)
ROCKBOND MASONRY COATING (RB MC)
ROCKBOND ANTI-CARBONATION COATING (RB ACC)
ROCKBOND ACRYLIC COATING (RB AC)

FURTHER INFORMATION:

Should you require further information on this product, or details of other ROCKBOND SPECIAL CONCRETE PRODUCTS, then please do contact our Technical Department:

Gilbert Cox BSc, Technical Director, Rockbond SCP Ltd., Newton's Farm Estate, Wissington, Nayland, Suffolk, CO6 4LX, England.	Telephone: 01206 265116, Email: info@rockbond.co.uk Website: www.rockbond.co.uk
---	--

<https://rockbond.co.uk/rockbond-products-safety-data-sheets/>

IMPORTANT NOTE:

ROCKBOND SCP LTD provides the above information in good faith and without warranty. The data represents typical values which can be updated at any time, and this information supersedes previous issues. No liability can be accepted for any damage or loss arising from the use of ROCKBOND SCP LTD literature or its products, because the company has no continuous control on how the products are mixed, placed or cured.

JANUARY 2024