

FORMULATORS, MANUFACTURERS AND CONSULTANTS OF SPECIAL CONCRETE PRODUCTS

Newton's Farm Estate, Wissington, Nayland, Suffolk.CO6 4LX, England

Telephone: 01206 265116 Email: info@rockbond.co.uk

Website: www.rockbond.co.uk

ROCKBOND MATERIAL SAFETY DATA SHEET

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION/COMPANY.

PRODUCT: ROCKBOND CEMENTITIOUS MORTARS AND GROUTS

COMPANY: Rockbond SCP Ltd.,
Newton's Farm Estate,
Wissington, Nayland,
Suffolk, CO6 4LX, England.

Telephone: 01206 265116,

Email: info@rockbond.co.uk

Website: www.rockbond.co.uk

2. COMPOSITION/INFORMATION ON INGREDIENTS.

Blends of special cement powders and sands.

3. HAZARDS IDENTIFICATION.

Irritant. Contains Portland cement. Powders produce alkaline solutions. Avoid contact with the skin and eyes. **TREAT THE CEMENTITIOUS MORTAR OR GROUT AS YOU WOULD FOR PORTLAND CEMENT SAND MORTAR OR SAND GROUT.**

Beware Rockbond Heavy Duty Industrial Floor Screed (RB HDIFS) and the Underwater Mortar AR (RB UWM AR) contain sharp steel fibres which may puncture the skin and eyes.

4. FIRST AID MEASURES.

Inhalation: If irritation occurs, move the patient to fresh air. In cases of inflammation, seek medical advice.

Skin: If skin contact occurs, immediately wash the affected area with soap and water. If irritation, soreness or other skin problems occur, seek medical advice.

Eyes: In the event of eye contact, irrigate the eyes quickly and thoroughly with plenty of clean water. In severe cases seek medical advice without delay.

Ingestion: If swallowed, do not induce vomiting, but wash out the mouth, and give the patient 2 or 3 glasses of water to drink. If large amounts have been swallowed, or symptoms develop, seek medical advice.

5. FIRE FIGHTING MEASURES.

Not applicable. Powders are non flammable.

6. ACCIDENTAL RELEASE MEASURES.

Treat as a common mess. Sweep up and clear up the powder with a broom, dustpan and brush, and dispose of sensibly. Wear protective clothing. The use of water is not recommended.

ROCKBOND MATERIAL SAFETY DATA SHEET.

CEMENTITIOUS MORTARS AND GROUTS CONTINUED..

7. HANDLING AND STORAGE.

Wear protective clothing. Store in a cool, dry, dark place.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION.

Exposure Limits:	Total inhalable dust - 10mg/m ³ 8 hour time weighted average. Respirable dust - 5mg/m ³ 8 hour time weighted average.
Engineering Methods:	Dust can cause irritation. Use in well ventilated areas, or install dust extraction systems to carry dust away from operatives.
Personal Protection:	Avoid ingestion by taking sensible precautions: where airborne dust is present, wear a dust mask. Goggles MUST be worn whenever there is a risk of the cement powder, or water/cement mixes, entering the eyes. Protective clothing MUST be worn, particularly gloves, that are effective at keeping out sharp steel fibres, cement dust and water. Whenever airborne cement powder is present, dust masks MUST be worn, particularly if the exposure is prolonged.

9. PHYSICAL AND CHEMICAL PROPERTIES:

Appearance:	Powder (max particle size, 1.7mm)	Flash point:	Not applicable
Colour:	White, light to dark grey	Flammability:	Not applicable
Odour:	Slight	Explosive properties:	Not applicable
pH wet powders	13 to 14	Oxidising properties:	None
Boiling point:	Not applicable	Vapour pressure:	Not applicable
Melting point:	Not applicable	Bulk density:	700 to 1600kg/m ³
		Solubility in water:	Mostly insoluble

10. STABILITY AND REACTIVITY.

Stability:	Stable.
Materials and conditions to avoid:	Reacts vigorously with strong acids
Hazard decomposition products:	None known.

11. TOXICOLOGICAL INFORMATION.

Inhalation:	Can cause irritation of mucous membranes and respiratory tract.
Skin:	Contact with the skin may cause irritation and, in severe cases, alkali burns.
Eyes:	Can cause irritation and inflammation to the eyes. In severe cases, there is a risk of permanent damage.
Ingestion:	May cause irritation of the mouth, throat and gastrointestinal tract.

12. ECOLOGICAL INFORMATION.

Can be harmful to fish and aquatic organisms in high concentrations. Generally greater than 200mg of powder per litre of water in closed environments where there is long and continuous contact.

13. DISPOSAL CONSIDERATIONS:

Dispose of as a controlled waste, and to local authority regulations.

ROCKBOND MATERIAL SAFETY DATA SHEET.

CEMENTITIOUS MORTARS AND GROUTS CONTINUED...

14. TRANSPORT INFORMATION.

Not classified as a hazardous material for transportation.

15. REGULATORY INFORMATION.

Classification for supply: Irritant. Risk phases: Irritant to skin. Risk of serious damage to eyes.

Safety phases: Wear suitable clothing to protect skin and eyes, particularly when using the Rockbond Heavy Duty Industrial Floor Screed (RB HDIFS) and the Rockbond Underwater Mortar Steel Reinforced (RB UWM SR) which contain sharp steel fibre ends which may puncture the skin and hurt the eyes. Should the powder come into contact with the eyes, rinse immediately with water and seek medical advice. Keep out of the reach of children.

16. OTHER INFORMATION.

The safety data sheet applies to the following ROCKBOND MORTARS AND GROUTS:

REPAIR MORTAR (RM)	FASTROCK GROUT (FRG)
LIGHTWEIGHT MORTAR (LWM) SERIES	FASTROCK ACCELERATED GROUT (FRAG)
REPAIR GROUT (RG),	WATERSTOP MORTAR (WSM)
REPAIR GROUT (ACRYLIC ENHANCED) (RGAE)	UNDERWATER PUTTY (UWP) SERIES
REPAIR GROUT PIGMENTED (RGP)	UNDERWATER MORTAR (UWM)
SUPERFLOW GROUT (SFG)	UNDERWATER MORTAR AR (UWM AR)
SUPER STRENGTH GROUT (SSG)	UNDERWATER ACCELERATED MORTAR (UWAM)
LIGHTWEIGHT GROUT (LWG) SERIES	UNDERWATER SA MORTAR (UWSAM)
FLOOR LEVELLING COMPOUND (FLC)	UNDERWATER GROUT (UWG)
INDUSTRIAL FLOOR SCREED (IFS) SERIES	PRESSURE POINTING MORTARS (PPM)
HEAVY DUTY INDUSTRIAL FLOOR SCREED (HDIFS)	HIGH DENSITY MORTARS/GROUTS (HDM/HDG)
BASE SCREED (BS)	SUPER DENSITY MORTARS/GROUTS (SDM/SDG)
FERROPLATE FLOOR TOPPING (FPFT)	SPRAYED RENDER (SR)
ROCKBOND TOP FLOOR TOPPING (RBT FT)	JOINTING COMPOUND (JC)
FASTROCK MORTAR (FRM)	HYDRAULIC LIME MORTAR (HLM)
FASTROCK ACCELERATED MORTAR (FRAM)	HERTITAGE T GROUT (HTG)
FASTROCK SUPER ACCELERATED MORTAR (FRAM)	TANKING MIX RENDER/GROUT (RB TMR/TMG)

FURTHER INFORMATION:

Should you require further information on this product, or details of other ROCKBOND SPECIAL CONCRETE PRODUCTS, then please do contact our Technical Department:

Gilbert Cox BSc,	Telephone: 01206 265116,
Technical Director,	Facsimile: 01206 265117,
Rockbond SCP Ltd.,	Email: info@rockbond.co.uk
Newton's Farm Estate,	Website: www.rockbond.co.uk
Wissington, Nayland, Suffolk, CO6 4LX, England.	

<https://rockbond.co.uk/rockbond-products-safety-data-sheets/>

IMPORTANT NOTE:

ROCKBOND SCP LTD provides the above information in good faith and without warranty. The data represents typical values which can be updated at any time, and this information supersedes previous issues. No liability can be accepted for any damage or loss arising from the use of ROCKBOND SCP LTD literature or its products, because the company has no continuous control on how the products are mixed, placed or cured.

SEPTEMBER 2025